



PVC Suction & Delivery Hose





Material Type:	 .PV0	C Suc	tion & Delivery Hose
Code			•
Temperature Range	 		10 - +60°
Colour			

Completely free of phthalates. Resistant to several chemicals and to weather conditions.

New formulation suitable for coveying milk and dairy products.

Suitable to deliver foodstuffs according to Reg. EU 10/2011 and FDA CFR 21 Item 176.170

Inside Ø	Outside Ø	Weight	WP	BP	Vacuum	Bend Radius
mm	mm	g/m	Bar	Bar	m H20	mm
12	18	215	7.0	35	8.5	50
20	27	360	6.0	30	8.5	90
25	33	520	6.0	30	8.5	110
32	40.4	675	5.0	25	8.5	140
38	47	830	5.0	25	8.5	170
40	49	865	5.0	25	8.5	180
50	60	1290	4.0	20	8	230
63	74.8	1855	3.5	17.5	8	280
76	88.2	2310	3.5	17.5	7	340
80	92.2	2420	3.5	17.5	7	360
90	103	3110	3.0	15	7	410
102	115	3490	2.0	10	7	460
127	144.4	5550	1.2	6	9	640
151	168.6	6935	1.2	6	9	760

Care should be taken in selecting the most suitable quality for each application.

Advice is available from the sales team but final responsibility remains with the customer.